

CO₂ INCUBATOR

Managing, Optimal Environmental for Cell Growth

Co₂ Incubator (LMX-CI)



Pre-Order Selection Options For Research and cell growth

- UV lamp for air jacket.
- Heat Sterilization - 120°C to 180°C.
- Co₂ and O₂ Gas Sensor.
- Water Jacketed.
- Touch Screen Display.
- Fan less design to reduce chance of contamination, reduce noise.
- Fan with in chamber HEPA for better recovery and ISO class 5 clean air Or higher.

Co₂ Incubator (LMX-HI)

TRI-GAS Incubator - Co₂, O₂ and N₂



Carbon dioxide (CO₂) incubators provide optimal growing conditions and contamination prevention for valuable cell cultures. LUXMED provides a wide range of CO₂ incubators, ranging from a small capacity and volume to a large scale capacity cabinet. All the CO₂ incubators are build with the patented Water Jacket and Air Jacket systems, which minimizes the risk of condensation at the present and in the future.

Features:

- Water tank for humidity in the chamber.
- Air jacket: equipped with UV Lamp for sterilizing; Water jacket: equipped with HEPA filter.
- Equipped with USB port and LCD Display, the incubator can save data in real time.
- High quality CO₂ gas filter ensures the inside gad quality.
- SMC brand gas circuit valves ensure more stable CO₂ concentration and less consumption of CO₂ gas.
- Microcomputer controller, LED displays temperature, CO₂ concentration ,run-time and timing.
- High quality infrared sensor for accurate CO₂ concentration.
- The working chamber adopts round angle structure , easy to clean.



Models:

Model	LMX-C50	LMX-C80	LMX-C160	LMX-C160	LMX-C160
Capacity	50L	80L	160L	160L	160L
Heating	Air jacket	Air jacket	Water jacket	Air jacket	Water jacket
Temp. Range	RT +5 ~ 60°C				
Control Type	Microcomputer controller				
Temp. Fluctuation	≤ ±0.2°C(at 37°C)				
Temp. Uniformity	≤ ±0.3°C(at 37°C)				
Time Setting	999h or continuous				
Alarm	Audible and visual alarm;Over-temperature alarm;CO ₂ Concentration alarm.				
Shelves	2 pcs/ adjustable				
Material	External cold-rolled steel with painting; internal stainless steel				
Door	With inner door and external door				
CO ₂ Range	Infrared sensor, range 0~20%				
CO ₂ Control Resolution	0.10%				
Humidification Type	Water tank for natural evaporation				
Sterilization Type	UV lamp for air jacket				
Ambient Temp. & Humidity	18~30°C,suggest 2±2°C; relative humidity ≤80%				
Caster	Footmaster caster				
Consumption	350W	600W	875W	650W	1000W
Power Supply	AC110/220V±10%, 50/60Hz				
Internal Size(W*D*H)mm	368*387*408	398*446*498	380*450*590	498*546*678	498*480*722
External Size(W*D*H)mm	500*527*821	600*596*921	628*543*1033	700*666*1101	747*654*1260
Packing Size(W*D*H)mm	655*680*970	730*735*1070	680*780*1220	790*830*1250	780*880*1420
Gross Weight(kg)	69	83	109	109	146